

BATTERY CHARGER MB1000-xx

- the battery chargers of the series MB1000



MB1000-12NP TWIN-Charger for 2xNP1 battery

MB1000-20SR TWIN Charger for
2 x ARRIFLEX SR3 batteries
MB-1000-12 UNIVERSAL-CHARGER

THE EXTERNAL CHARGER MB1000-xx for NiCd- and NiMH batteries

These approved charging electronics, which are built in the power belts, since several years, are also available as external chargers.

The battery chargers of the series MB1000 are for recharge NiCad (Nickel-Cadmium) and for NiMH (Nickel-Metall-Hydrid). There is a complete series of chargers available.

UNIVERSAL CHARGER MB1000-12 for battery 12V - 14,4V with XLR connector

TWIN CHARGER MB1000-12 for 2 x batteries 12V - 14,4V with 2 x XLR connector

UNIVERSAL CHARGER MB1000-20 for battery >15V - 26,6V with XLR connector

TWIN CHARGER MB1000-20 for 2 x batteries >15V - 26,6V mit 2 x XLR connector

TWIN CHARGER MB1000-12SR for 2 x batteries ARRIFLEX 16SR2

TWIN CHARGER MB1000-20 SR for 2 x batteries ARRIFLEX SR3

TWIN CHARGER MB1000-12NP for 2 x batteries SONY NP1 or 2 x batteries SONY BP-90

The TWIN CHARGER MB1000-xx is two charging units in one housing, which have only a common AC input. If one charger is out of order the second charging unit can be used to recharge a battery.

Specification for

**MB1000-12, MB1000-20, TWIN MB1000-12, TWIN MB1000-20, TWIN MB1000-12SR,
TWINMB1000-12SR2, TWIN MB1000-20SR3 TWIN MB1000-12NP**

Housing: Aluminium-Profile Housing
Charging-Method: - Δ Voltage with additional safety timer
Charging time max.: 4 - (11) h (factory adjusted)
Trickle charge: pulsed trickle charge 10mAh
Special: electronic reverse polarity safety
LED green for: charge, trickle charge, deep discharged, battery defect warning (by different LED flushing mode)
LED red for: reverse polarity warning

CODE-NO	DESCRIPTION	TYPE	VOLT DC	VOLT AC	CHARGING CURRENT	TRICKLE	- Δ V	SAFETY TIMER (h)	REVERSE POLARITY SAFETY	CONNECTOR	WEIGHT	MASUREMENTS (lxwxh)mm
5931152	UNIVERSAL-CHARGER MB1000-12	NiCd/NiMH	-14,4V	85-264V	1Ah	pulsed	•	9	•	1 x XLR4	800g	168x110x54
5931153	UNIVERSAL-CHARGER MB1000-12	NiCd/NiMH	-14,4V	85-264V	1Ah	pulsed	•	9	•	1 x XLR5	800g	168x110x54
5931154	TWIN-CHARGER MB1000-12	NiCd/NiMH	2 x -14,4V	2 x 85-264V	2 x 1Ah	pulsed	•	9	•	2 x XLR4	950g	168x110x54
5931155	TWIN-CHARGER MB1000-12	NiCd/NiMH	2 x -14,4V	2 x 85-264V	2 x 1Ah	pulsed	•	9	•	2 x XLR5	950g	168x110x54
5931159	UNIVERSAL-CHARGER MB1000-20	NiCd/NiMH	1 x -26,4V	85-264V	1 x 1Ah	pulsed	•	9	•	1 x XLR4	800g	168x110x54
5931160	UNIVERSAL-CHARGER MB1000-20	NiCd/NiMH	1 x -26,4V	85-264V	1 x 1Ah	pulsed	•	9	•	1 x XLR5	800g	168x110x54
5931161	TWIN-CHARGER MB1000-20	NiCd/NiMH	2 x -26,4V	2 x 85-264V	2 x 1Ah	pulsed	•	9	•	2 x XLR4	950g	168x110x54
5931162	TWIN-CHARGER MB1000-20	NiCd/NiMH	2 x -26,4V	2 x 85-264V	2 x 1Ah	pulsed	•	9	•	2 x XLR5	950g	168x110x54
5931158	TWIN-CHARGER MB1000-20SR3	NiCd/NiMH	2 x -26,4V	2 x 85-264V	2 x 1Ah	pulsed	•	4	•	2 x SR3	950g	168x110x54
5931157	TWIN-CHARGER MB1000-12SR2	NiCd/NiMH	2 x -14,4V	2 x 85-264V	2 x 1Ah	pulsed	•	4	•	2 x SR2	950g	168x110x54
5931168	TWIN-CHARGER MB1000-12SR2	NiCd/NiMH	2 x -14,4V	2 x 85-264V	2 x 1Ah	pulsed	•	4	•	2 x 3-pin. for DC-accessory connector	950g	168x110x54
5931164	TWIN-CHARGER MB1000-12NP	NiCd/NiMH	2 x -14,4V	2 x 85-264V	2 x 1 Ah	pulsed	•	6	•	2 x NP-1/ 2 x BP-90 connector	1300g	260x110x54

SPECIFICATION SUBJECT TO CHANGE WITHOUT PRIOR NOTICE!